

Calbrite™

Stainless Steel Conduit Systems

Stainless Steel Box Connectors

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Machined tapered male threads by machined smooth bore inside diameter
- No package qty. required

Certifications and Compliances:

Calbrite stainless steel box connectors are fabricated to UL and ASTM standards.

Applications:

Used to connect a box or enclosure to the conduit coupling. It can also be used with a locknut to connect two boxes side by side, or back to back and with a locknut to connect fixture housings in continuous runs.

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments



Size	Part Number	Inner Diameter	Height	Hex Nut Thickness	Thread Length	Weight (ea) per lb.
1/2"	S60500CH00	.580"	.860"	.250"	.500"	0.19
3/4"	S60700CH00	.790"	.900"	.258"	.570"	0.25
1"	S61000CH00	1.000"	1.050"	.320"	.610"	0.45
1-1/4"	S61200CH00	1.390"	1.200"	.370"	.750"	0.67
1-1/2"	S61500CH00	1.580"	1.300"	.400"	.820"	0.72
2"	S62000CH00	2.050"	1.450"	.430"	.880"	1.08
2-1/2"	S62500CH00	2.380"	1.575"	.500"	.910"	1.91
3"	S63000CH00	3.000"	1.740"	.500"	1.050"	2.43
4"	S64000CH00	3.890"	1.980"	.600"	1.200"	4.09

*All dimensions are for informational purposes only *Tolerances +/- 5%*