

Stainless Steel Split Ring Clamps

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless rigid, stainless light wall, aluminum, galvanized, and PVC Coated conduit
- No package qty. required



Certifications and Compliances:

Calbrite stainless steel Split Ring Clamps are fabricated to UL and ASTM standards. Complies with Manufacturers' Standardization Society MSS SP-58 and SP-69

Applications:

Type 316 stainless steel Split Ring Clamps are designed for securing and mounting conduit, horizontally or vertically, away from the wall or device in washdown or corrosive environments.



Industries Commonly Served:

- Food & Beverage Production & Distribution
- Dairy Product Processing
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Plants
- Along with other corrosive environments

Size	Part Number	A (Height)	B (Length)	C	D Female Thread	E (Bolt Size)	Thick-ness	Weight (ea) per lb.
1/2"	S60500SP00	1.20"	2.18"	0.75"	0.375"	#10 x 1/2"	0.53"	0.09
3/4"	S60700SP00	1.41"	2.46"	1.00"	0.375"	#10 x 1/2"	0.53"	0.11
1"	S61000SP00	1.73"	2.83"	1.24"	0.375"	#10 x 1/2"	0.53"	0.14
1-1/4"	S61200SP00	2.14"	3.20"	1.61"	0.375"	#10 x 1/2"	0.53"	0.18
1-1/2"	S61500SP00	2.36"	3.44"	1.83"	0.375"	#10 x 1/2"	0.53"	0.20
2"	S62000SP00	2.87"	3.92"	2.34"	0.375"	#10 x 1/2"	0.53"	0.23

All dimensions are for informational purposes only *Tolerances +/- 5%