

Calbrite™

Stainless Steel Conduit Systems

Stainless Steel EMT Compression Coupling

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless EMT conduit
- Addition of stainless and plastic ferrule assures weatherproof seal
- Connectors assembled with ferrules, no separate pieces to purchase or stock
- No package qty. required



Certifications and Compliances:

Calbrite stainless steel EMT fittings and accessories are fabricated to UL standards
NEMA 4X approved

Material:

Body: 316SS
Stainless Ferrule: 316SS
Red Ferrule: Nylon

Applications:

Used to join two lengths of stainless EMT.



Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments

Size	Part Number	A	B	C	D	I.D.	Wt. ea per lb.
1/2"	S20500CC00	2.130"	1.050"	1.350"	.540"	.710"	0.16
3/4"	S20700CC00	2.050"	1.290"	1.350"	.540"	.930"	0.21
1"	S21000CC00	2.200"	1.580"	1.500"	.570"	1.170"	0.31
1-1/4"	S21200CC00	2.560"	1.960"	1.770"	.570"	1.510"	0.47
1-1/2"	S21500CC00	2.700"	2.240"	1.900"	.610"	1.740"	0.63
2"	S22000CC00	2.880"	2.735"	2.125"	.650"	2.200"	0.83

*All dimensions are for informational purposes only *Tolerances +/- 5%*