

Calbrite™

Stainless Steel Conduit Systems

Stainless Steel Male Compression Connector

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Addition of stainless and plastic ferrule assures weatherproof seal
- Connectors assembled with ferrules, no separate pieces to purchase or stock
- No package qty. required



Certifications and Compliances:

Calbrite stainless steel compression connectors are fabricated to UL standards
NEMA 4X approved

Material:

Body: 316SS

Stainless Ferrule: 316SS

Yellow Ferrule: Nylon


Applications:

Used to join stainless light wall or rigid conduit to a box, enclosure, or other fittings.

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments

Suitable for Damp Locations



Size	Part Number	A	B	I.D.	Wt. ea per lb.
1/2"	S60500MC00	1.670"	1.200"	.850"	0.11
3/4"	S60700MC00	1.860"	1.450"	1.065"	0.16
1"	S61000MC00	2.000"	1.750"	1.330"	0.23
1-1/2"	S61500MC00	2.380"	2.390"	1.930"	0.33
2"	S62000MC00	2.530"	2.920"	2.440"	0.45

All dimensions are for informational purposes only *Tolerances +/- 5%