


# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel EMT Conduit

#### Features:

- Manufactured in type 304 & 316 stainless to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting & bacterial corrosion
- Calbrite is the exclusive manufacturer of stainless EMT conduit & fittings
- Stainless steel EMT weighs 57% less than stainless steel rigid conduit and 43% less than light wall
- Stainless steel EMT requires no threading and is joined together by utilizing Calbrite EMT compression fittings



#### Certifications and Compliances:

Calbrite™ stainless EMT conduit is manufactured to UL797 standards and meets ANSI C80.3

Manufactured in the United States

#### Applications:

Calbrite™ stainless steel EMT conduit and fittings, combine strength with ductility, resulting in a lightweight and easy-to-handle conduit assembly. EMT can be installed indoors and outdoors in accordance with NEC, providing it will not be subject to severe physical damage during and after installation.

Calbrite stainless steel EMT provides superior performance in applications subject to corrosive environments, harsh chemical treatments, and required wash-downs. In addition to the ease of installation and maintenance, stainless steel is 100% recyclable. Calbrite EMT enhances the appearance and the surface's resistance to pitting & bacterial corrosion in CIP (clean-in-place) and SIP (sterilize-in-place) systems.

#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations

Trade Size	Outside Diameter	Inside Diameter	Ft/ Wt.	Type 304 Part Number 10' Length	Type 316 Part Number 10' Length	Type 304 Part Number 5' Length	Type 316 Part Number 5' Length
1/2"	0.706"	0.622"	0.30	S10510CT00	S20510CT00	S10505CT00	S20505CT00
3/4"	0.922"	0.824"	0.46	S10710CT00	S20710CT00	S10705CT00	S20705CT00
1"	1.163"	1.050"	0.67	S11010CT00	S21010CT00	S11005CT00	S21005CT00
1-1/4"	1.510"	1.380"	1.01	S11210CT00		S11210CT00	
1-1/2"	1.740"	1.610"	1.16	S11510CT00		S11510CT00	
2"	2.200"	2.067"	1.48	S12010CT00		S12010CT00	

All dimensions are for informational purposes only \*Tolerances +/- 5%