

# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel Light Wall Conduit

#### Features:

- Manufactured in type 304 & 316 stainless to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting & bacterial corrosion
- No special tools are required for installation
- Lighter weight provides cost savings on installation and shipping
- Any custom size available up to 20' in length

#### Certifications and Compliances:

Calbrite™ light wall conduit is manufactured to the highest standards of the American National Standards Institute (ANSI) and Underwriters Laboratories (UL)  
Manufactured in the US



#### Applications:

Calbrite™ stainless steel Light Wall Conduit is an equivalent to a non-threaded stainless IMC conduit. Calbrite's Light Wall conduit is more impact resistant compared with EMT and is 100% recyclable. With its lighter weight, precise tolerances, and ease of installation attributes, stainless steel Light Wall is often specified in corrosive environments and subjected to harsh chemical treatments or washdown.

Light Wall Conduit is manufactured without threads, and is joined together by utilizing compression fittings for labor cost savings and simplified installations. Light Wall Conduit is easily cut and bent using standard tools.

#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites

Trade Size	Type 304 Part Number	Type 316 Part Number	Outer Diameter	Inner Diameter	Weight per ft. (lbs.)
1/2"	S50510CT00	S70510CT00	0.840"	0.670"	0.67
3/4"	S50710CT00	S70710CT00	1.050"	0.884"	0.86
1"	S51010CT00	S71010CT00	1.315"	1.097"	1.40
1-1/2"	S51510CT00	S71510CT00	1.900"	1.682"	2.09
2"	S52010CT00	S72010CT00	2.375"	2.157"	2.64

*All dimensions are for informational purposes only \*Tolerances +/- 5%*