

Calbrite™

Stainless Steel Conduit Systems

Stainless Steel Bare Flex Conduit

Features:

- Excellent strength and durability
- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance & aesthetic appearance
- Extremely flexible with smooth interior ease of installation and wire pull thru
- Compatible with Calbrite™ stainless steel flex connectors & 90's
- Interlock (double buckle) style
- Manufactured in 25' coils



Certifications and Compliances:

Calbrite™ bare flexible conduit is manufactured to comply with UL514B standards. Manufactured in the United States

Applications:


Flexible stainless steel conduit can be used for protecting electronic and electrical wires, and cable. Suitable for corrosive environments, including pumps, motors, HVAC systems, machine tools, electrical housings, and cabinetry. Good absorption of motion and vibration.



Double Buckle

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments



Trade Size	Part Number	Outside Diameter	Inside Diameter	Bend Radius	Weight per 25' Coil (lbs.)
1/2"	S40500CTFX	0.744"	0.610"	4"	4
3/4"	S40700CTFX	0.960"	0.790"	4-1/2"	7
1"	S41000CTFX	1.160"	1.010"	6"	10
1-1/4"	S41200CTFX	1.330"	1.500"	7-1/2"	13
1-1/2"	S41500CTFX	1.750"	1.520"	9"	22

All dimensions are for informational purposes only *Tolerances +/- 5%