



## STAINLESS STEEL MALE COMPRESSION CONNECTORS

### Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless rigid and IMC
- Addition of stainless and plastic ferrules assures weatherproof seal
- Connectors assembled with ferrules, no separate pieces to purchase or stock
- No package qty. required


### Certifications and Compliances:

- Calbrite stainless steel compression connectors are fabricated to meet UL standards
- NEMA 4X approved

### Material:

- Body: 316SS
- Stainless Ferrule: 316SS
- Yellow Ferrule: Nylon

Suitable for Damp Locations



### Applications:

Used to join stainless steel non-threaded conduit to a box, enclosure or other fittings.

### Industries Commonly Served:

- Food & Beverage Production
- Marine & Coastal Facilities
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Pulp & Paper Mills
- Along with other corrosive environments

Part Number	Size	A	B	I.D.	Weight each per lb
S60500MC00	1/2"	1.710"	1.200"	0.850"	0.18
S60700MC00	3/4"	1.880"	1.450"	1.065"	0.28
S61000MC00	1"	2.030"	1.750"	1.330"	0.40
S61500MC00	1-1/2"	2.350"	2.390"	1.930"	0.70
S62000MC00	2"	2.600"	2.900"	2.400"	1.12

*All dimensions are for informational purposes only \*Tolerances +/- 5%*