



STAINLESS STEEL COMPRESSION UNIONS (COUPLINGS)

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless rigid and IMC
- Addition of stainless and plastic ferrules assures weatherproof seal
- Connectors assembled with ferrules, no separate pieces to purchase or stock
- No package qty. required

Certifications and Compliances:

- Calbrite stainless steel compression connectors are fabricated to meet UL standards
- NEMA 4X approved

Material:

- Body: 316SS
- Stainless Ferrule: 316SS
- Yellow Ferrule: Nylon

Applications:

Used to join two lengths of stainless steel conduit.

Industries Commonly Served:

- Food & Beverage Production
- Marine & Coastal Facilities
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Pulp & Paper Mills
- Along with other corrosive environments

Part Number	Size	A	B	I.D.	Weight each per lb
S60500CC00	1/2"	2.150"	1.200"	.850"	0.26
S60700CC00	3/4"	2.430"	1.450"	1.065"	0.42
S61000CC00	1"	2.650"	1.750"	1.330"	0.60
S61500CC00	1-1/2"	3.000"	2.390"	1.930"	1.06
S62000CC00	2"	3.000"	3.000"	2.440"	1.76

*All dimensions are for informational purposes only *Tolerances +/- 5%*

