



STAINLESS STEEL REDUCING (FACE) BUSHINGS

Features:


- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- NPT Male by NPSM Female Threads
- No package qty. required

Certifications and Compliances:

- Manufactured in strict accordance to blue print, UL 514B standards, NEC Code Compliance and pertinent requirements issued by Calpipe Industries

Applications:

Designed for use with stainless steel conduit, to reduce sizes of threaded stainless conduit, nipples and other threaded fittings.



Industries Commonly Served:

- Food & Beverage Production
- Marine & Coastal Facilities
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Pulp & Paper Mills
- Along with other corrosive environments

Part Number	Size	A (Height)	B (Width)	Wall Thickness	Weight each per lb
S60700FB05	3/4" x 1/2"	.750"	1.010"	.013"	0.05
S61000FB05	1" x 1/2"	.760"	1.280"	.250"	0.14
S61000FB07	1" x 3/4"	.760"	1.290"	.160"	0.07
S61200FB05	1-1/4" x 1/2"	1.000"	1.630"	.430"	0.40
S61200FB07	1-1/4" x 3/4"	1.000"	1.640"	.330"	0.32
S61200FB10	1-1/4" x 1"	1.000"	1.640"	.210"	0.18
S61500FB05	1-1/2" x 1/2"	1.000"	1.860"	.556"	0.60
S61500FB07	1-1/2" x 3/4"	1.000"	1.870"	.445"	0.50
S61500FB10	1-1/2" x 1"	1.020"	1.870"	.320"	0.36
S61500FB12	1-1/2" x 1-1/4"	1.025"	1.880"	.160"	0.14
S62000FB05	2" x 1/2"	1.020"	2.360"	.800"	1.06
S62000FB07	2" x 3/4"	1.000"	2.360"	.700"	0.92
S62000FB10	2" x 1"	1.000"	2.360"	.560"	0.79
S62000FB12	2" x 1-1/4"	1.000"	2.360"	.400"	0.58
S62000FB15	2" x 1-1/2"	1.020"	2.360"	.280"	0.38

All dimensions are for informational purposes only *Tolerances +/- .5%