

STAINLESS STEEL TECK CONNECTORS

Features:

- Manufactured in type 304 stainless steel for increased corrosion resistance
- One Piece Compact Design
- Unique Grounding Seal for superior connectivity
- No disassembly required for easy and fast installations
- Neoprene bushing provides pull out and sealing protection

Certifications and Compliances:

- NEMA 4, IP65

Applications:

Calbrite stainless steel TECK connectors feature a one piece design, requires no disassembly and are designed to form a watertight seal around the jacketed metal cable and at the enclosure entry. Rated NEMA 4 and IP 65, these connectors are in-stock in 1/2 to 4 hub sizes. Also available in 316 stainless steel upon request.

Industries Commonly Served

- Food and Beverage Production
- Pharmaceuticals and Cosmetics
- Marine and Coastal Facilities
- Chemical Plants
- Water and Wastewater Treatment
- Refining and Extraction Sites
- Petrochemical Operations
- Pulp and Paper Mills
- Along with other corrosive environments



Hub Size (in)	Part Number	Exposed Armor Length (in)	Cable Range Over Jacket (in)		Cable Range Over Armor (in)		Dimension A (in)	Dimension B (in)
			Min	Max	Min	Max		
1/2	S40501TKOO	7/8	.525	.650	.415	.570	2.10	1.53
1/2	S40502TKOO	7/8	.650	.775	.540	.695	2.10	1.53
1/2	S40503TKOO	7/8	.750	.875	.640	.795	2.10	1.53
1/2	S40504TKOO	7/8	.860	.985	.750	.905	2.10	1.53
3/4	S40705TKOO	1	.955	1.080	.845	1.000	2.45	2.20
3/4	S40706TKOO	1	1.080	1.205	.970	1.125	2.45	2.20
1	S41007TKOO	1	1.205	1.350	1.095	1.270	2.45	2.47
1 1/4	S41208TKOO	1 1/4	1.350	1.475	1.240	1.395	3.35	2.97
1 1/4	S41209TKOO	1 1/4	1.475	1.600	1.365	1.520	3.35	2.97
1 1/4	S41210TKOO	1 1/4	1.600	1.725	1.490	1.645	3.35	2.97
1 1/2	S41511TKOO	1 1/2	1.725	1.850	1.615	1.770	3.70	3.50
1 1/2	S41512TKOO	1 1/2	1.850	1.975	1.740	1.895	3.70	3.50
1 1/2	S41513TKOO	1 1/2	1.975	1.865	2.020	2.020	3.70	3.50
2	S42014TKOO	1 3/4	2.100	2.225	1.990	2.145	4.05	4.15
2	S42015TKOO	1 3/4	2.225	2.350	2.115	2.270	4.05	4.15
2	S42016TKOO	1 3/4	2.350	2.475	2.240	2.395	4.05	4.15
2	S42017TKOO	1 3/4	2.475	2.600	2.365	2.520	4.05	4.15
2	S42018TKOO	1 3/4	2.600	2.725	2.490	2.645	4.05	4.15
2 1/2	S42519TKOO	1 3/4	2.700	2.850	2.560	2.760	4.10	4.60
2 1/2	S42520TKOO	1 3/4	2.850	3.000	2.710	2.910	4.10	4.60
3	S43021TKOO	1 3/4	3.000	3.150	2.860	3.060	4.50	5.68
3	S43022TKOO	1 3/4	3.150	3.300	3.010	3.210	4.50	5.68
3	S43023TKOO	1 3/4	3.300	3.450	3.160	3.360	4.50	5.68
3 1/2	S43524TKOO	1 3/4	3.450	3.600	3.300	3.500	4.60	6.02
3 1/2	S43525TKOO	1 3/4	3.600	3.750	3.450	3.650	4.60	6.02
3 1/2	S43526TKOO	1 3/4	3.750	3.900	3.600	3.800	4.60	6.02
4	S44027TKOO	1 3/4	3.900	4.050	3.750	3.940	4.75	6.52
4	S44028TKOO	1 3/4	4.050	4.200	3.900	4.090	4.75	6.52
4	S44029TKOO	1 3/4	4.200	4.350	4.050	4.240	4.75	6.52