

STAINLESS STEEL THREE-PIECE COUPLINGS

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Designed for use with stainless threaded conduit
- Machined tapered female threads for smooth bore inside diameter
- No package quantity required





Certifications and Compliances:

- UL/cUL 514B Listed
- UL File # E308159
- CSA C22.2 No. 18.3
- Intended for installation in accordance with ANSI/NFPA 70, National Electrical Code (NEC)
- Intended for installation in accordance with CAN/CSA-C22.1, “Canadian Electrical Code, Part I”

Applications:

To join and connect threaded ends of stainless conduit where neither length of conduit can be turned.



Part Number	Trade Size (in)	A (in)	B (in)	C (in)	D (in)	E (in)	Female Thread ID (in)	Weight per each (lb)
S605003U00	½	1.535	1.680	0.800	0.750	1.240	0.840	0.45
S607003U00	¾	1.800	1.750	0.825	0.770	1.300	1.050	0.60
S610003U00	1	2.143	2.130	1.000	0.975	1.553	1.315	0.98
S612003U00	1¼	2.540	2.160	1.030	0.985	1.590	1.660	1.18
S615003U00	1½	2.870	2.161	1.030	0.985	1.600	1.900	1.50
S620003U00	2	3.525	2.200	1.040	1.000	1.630	2.375	2.27
S625003U00	2½	3.400	3.720	1.580	1.560	2.950	2.875	2.50
S630003U00	3	4.070	3.800	1.610	1.610	3.100	3.500	3.28
S640003U00	4	5.250	4.110	1.850	1.750	3.200	4.500	6.35

All dimensions are for informational purposes only *Tolerances +/- 5%

