

STAINLESS STEEL BOX CONNECTORS

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Machined tapered male threads by machined smooth bore inside diameter
- No package quantity required

Applications:

Used to connect a box or enclosure to the conduit coupling. It can also be used with a locknut to connect two boxes side by side, or back to back and with a locknut to connect fixture housings in continuous runs.



Part Number	Trade Size (in)	Inner Diameter (in)	Width (in)	Legth (in)	Hex Nut Thickness (in)	Thread Length (in)	Weight per each (lb)
S60500CH00	½	0.650	1.140	1.000	0.210	0.625	0.090
S60700CH00	¾	0.830	1.410	1.000	0.210	0.690	0.120
S61000CH00	1	1.140	1.720	1.290	0.275	0.900	0.150
S61200CH00	1 ¼	1.390	2.070	1.320	0.340	0.940	0.280
S61500CH00	1 ½	1.625	2.320	1.410	0.425	0.940	0.390
S62000CH00	2	2.000	2.830	1.420	0.440	0.940	0.590
S62500CH00	2 ½	2.450	3.400	1.920	0.450	1.380	0.980
S63000CH00	3	3.000	3.850	1.580	0.500	1.380	1.310
S64000CH00	4	3.970	5.120	2.000	0.500	1.440	1.570

All dimensions are for informational purposes only *Tolerances +/- 5%

