

STAINLESS STEEL SPLIT RING CLAMPS

Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished to a bright, easily maintainable finish that is modern, attractive, easy to clean, and that also enhances the surface's resistance to pitting and bacterial corrosion
- Designed for use with stainless steel Rigid / IMC, aluminum and galvanized conduit
- Two type 316 stainless steel bolts included
- No package quantity required



Applications:

Calbrite's stainless steel Split Ring Clamps are designed for mounting and securing conduit, horizontally or vertically, away from the wall or device in wash-down or corrosive environments when used with Calbrite's Mounting Plates and Extensions.

Part Number	Trade Size (in)	A Height (in)	B Length (in)	C Female Thread (in)	D Bolt Size (in)	Thickness (in)	Weight per each (lb)
S60500SP00	½	1.160	2.180	0.375	#10 x ½	0.125	0.090
S60700SP00	¾	1.410	2.500	0.375	#10 x ½	0.125	0.110
S61000SP00	1	1.750	2.700	0.375	#10 x ½	0.135	0.140
S61200SP00	1¼	2.030	3.230	0.375	#10 x ½	0.140	0.160
S61500SP00	1½	2.420	3.500	0.375	#10 x ½	0.150	0.200
S62000SP00	2	2.870	3.920	0.375	#10 x ½	0.150	0.230
S62500SP00	2½	3.650	5.000	0.500	¼ x 20	0.160	0.500
S63000SP00	3	4.250	5.760	0.500	¼ x 20	0.210	0.750
S64000SP00	4	5.300	6.830	0.500	¼ x 20	0.250	1.130

All dimensions are for informational purposes only *Tolerances +/- 5%

