

STAINLESS STEEL TECK CONNECTORS

Features:

- Manufactured in type 304 stainless steel for increased corrosion resistance
- One Piece Compact Design
- Unique Grounding Seal for superior connectivity
- No disassembly required for easy and fast installations
- Neoprene bushing provides pull out and sealing protection



Certifications and Compliances:

- NEMA 4, IP65
- CSA C22.2 No 18.3-13 Listed

Applications:

Calbrite stainless steel TECK connectors feature a one piece design, require no disassembly and are designed to form a watertight seal around the jacketed metal cable and at the enclosure entry. Rated NEMA 4 and IP65, these connectors are in-stock in ½" to 4" hub sizes. Also available in type 316 stainless steel upon request.

Hub Size (in)	Part Number	Exposed Armor Length (in)	Cable Range Over Jacket		Cable Range Over Armor		Length (in)	Width (in)
			Min (in)	Max (in)	Min (in)	Max (in)		
½	S40501TKOO	⅞	0.525	0.650	0.415	0.570	2.100	1.530
½	S40502TKOO	⅞	0.650	0.775	0.540	0.695	2.100	1.530
½	S40503TKOO	⅞	0.750	0.875	0.640	0.795	2.100	1.530
½	S40504TKOO	⅞	0.860	0.985	0.750	0.905	2.100	1.530
¾	S40705TKOO	1	0.985	1.080	0.845	1.000	2.450	2.200
¾	S40706TKOO	1	1.080	1.205	0.970	1.125	2.450	2.200
1	S41007TKOO	1	1.205	1.350	1.095	1.270	2.450	2.47
1¼	S41208TKOO	1¼	1.350	1.475	1.240	1.395	3.350	2.970
1¼	S41209TKOO	1¼	1.475	1.600	1.365	1.520	3.350	2.970
1¼	S41210TKOO	1¼	1.600	1.725	1.490	1.645	3.350	2.970
1½	S41511TKOO	1½	1.725	1.850	1.615	1.770	3.700	3.500
1½	S41512TKOO	1½	1.850	1.975	1.740	1.895	3.700	3.500
1½	S41513TKOO	1¾	1.975	1.865	2.020	2.020	3.700	3.500
2	S42014TKOO	1¾	2.100	2.225	1.990	2.145	4.050	4.150
2	S42015TKOO	1¾	2.225	2.350	2.115	2.270	4.050	4.150
2	S42016TKOO	1¾	2.350	2.475	2.240	2.395	4.050	4.150
2	S42017TKOO	1¾	2.475	2.600	2.365	2.520	4.050	4.150
2	S42018TKOO	1¾	2.600	2.725	2.490	2.645	4.050	4.150

All dimensions are for informational purposes only *Tolerances +/- 5%



STAINLESS STEEL TECK CONNECTORS

Hub Size (in)	Part Number	Exposed Armor Length (in)	Cable Range Over Jacket		Cable Range Over Armor		Length (in)	Width (in)
			Min (in)	Max (in)	Min (in)	Max (in)		
2½	S42519TKOO	1¾	2.700	2.850	2.560	2.760	4.100	4.600
2½	S42520TKOO	1¾	2.850	3.000	2.710	2.910	4.100	4.600
3	S43021TKOO	1¾	3.000	3.150	2.860	3.060	4.500	5.680
3	S43022TKOO	1¾	3.150	3.300	3.010	3.210	4.500	5.680
3	S43023TKOO	1¾	3.300	3.450	3.160	3.360	4.500	5.680
3½	S43524TKOO	1¾	3.450	3.600	3.300	3.500	4.600	6.020
3½	S43525TKOO	1¾	3.600	3.750	3.450	3.650	4.600	6.020
3½	S43526TKOO	1¾	3.750	3.900	3.600	3.800	4.600	6.020
4	S44027TKOO	1¾	3.900	4.050	3.750	3.940	4.750	6.520
4	S44028TKOO	1¾	4.050	4.200	3.900	4.090	4.750	6.520
4	S44029TKOO	1¾	4.200	4.350	4.050	4.240	4.750	6.520

All dimensions are for informational purposes only *Tolerances +/- 5%

